

PRODUCT CARD



PRODUCT CODE: OR-PSU-1642

EAN: 5908254803833

DIN rail power supply 12V DC 1.25A, 15W, width: 1 unit

Highly efficient and reliable DIN rail power supply of 15W max. load and 12V DC output voltage, which can be adjusted. It has been developed for DIN rail installation and can be used in vast number of applications, e.g. industrial applications, low voltage installations, such as CCTV or alarm systems. This power supply unit includes: overload protection, anti-surge protection and overvoltage protection. An integrated diode indicates activation of the device.

U

Output voltage:
12V DCV

U

Input voltage:
100-230V 50-60Hz

P

Rated power:
15W

Syme

Installation:
szyna DIN

Informacje ogólne

Short-circuit protection: yes

Voltage adjustment: yes

Current protection: yes

Voltage protection: yes

No. of modules (width): 1

Output voltage: 12V DC V

Input voltage: 100-230V 50-60Hz

Rated power: 15 W

Output current: 1.25 A

Max. short time current rating: 2,1A

Standby power consumption: 0,3 W

Over voltage category: III

Protection rating - IP: 20

Installation: szyna DIN

Dimensions - width: 18 mm

Dimensions - height: 58 mm

Dimensions - depth: 90 mm